

ASSEMBLY INSTRUCTIONS FOR YOUR BRIGHTON FLUSH MOUNT

IMPORTANT SAFETY INSTRUCTIONS:

- * These instructions are provided for your safety.
- * It is very important that they are read completely before beginning the installation of your fixture.
- * WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.
- * Turn off power at switch before replacing bulbs, making sure fixture has had sufficient time to cool down.
- * This fixture is UL rated for dry locations.

ASSEMBLY INSTRUCTIONS:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/ CIRCUIT BREAKER.
2. Remove all parts from carton and discard packing materials.
3. Place parts on a level surface. Remove canopy (C) from shade (G) by carefully removing clips (H) and releasing shade (G) from canopy (C).
4. Remove mounting plate (A) from canopy (C) by removing threaded spheres (F). Set threaded spheres (F) aside.
5. Affix mounting plate (A) to ceiling outlet box using mounting screws (B).
6. Lift canopy (C) to the ceiling and make the proper electrical connections noted in steps 7 - 9. **A licensed electrician is recommended.**
7. Attach ground wire from fixture (green or copper in color) to ground wire from outlet box. Fasten wires together with wire nut (J) and tightly wrap connection with electrical tape.
8. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (J). Wrap connection with electrical tape.
9. Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (J) and tightly wrap connection with electrical tape. Gently push wire connections back into the outlet box.
10. Lift canopy (C) over mounting plate (A). Screws in mounting plate (A) will protrude through holes in canopy (C). Use threaded spheres (F) to attach the canopy to the mounting plate.
11. Install (2) 40W MAX. Type A, medium base bulbs into the sockets (E).
12. Before attaching the shade to the fixture, note the stickers located at every notch (I) on shade. Notice the stickers at cutouts (D) and on clips (H). Shade notches must be aligned with corresponding sticker at cutouts. Stickers on clips must correspond to the shade and cutout stickers. For example, the cutout sticker labeled with a number 1 will line up with the notch that is labeled with a number 1 sticker. The clip labeled with a number 1 sticker will then be used to fasten the two together. Note: misaligning the stickers or using a clip that does not match may result in an incorrect fit which could cause the shade to fall.
13. Lift shade (G) up to canopy (C), aligning notches (I) with cutouts (D). Secure shade (G) to canopy (C) by attaching the bottom of clip (H) under the lip of shade (G) at notch (I). Push clip (H) into place over the rim of the canopy (C) and into cutout (D). Repeat this step for remaining clips.
14. Reconnect main electrical supply at the fuse box/ circuit breaker and test the fixture.

